

Modular Patch Panel

Telesafes modular patch panels are designed for flexible and user-friendly installation. Equipped with 4-port modules one panel can serve 4, 8, 12, 16, 20 or 24 users. When not in use, module openings in the panel can be closed by a cover plate.

Expanding or changing modules is easy, and by using the Telesafe Mounting Board (4710-501), the installation of modules and cable termination can be done from the front side of the rack.

The modular patch panels from Telesafe meet the electrical specifications of the latest ISO/IEC 11801 and CENELEC 50173 standards. Each of the panels may be installed in a mix-and-match Class D (100 MHz, "Cat.5e") cabling solution, or as one component in a Class E-250 MHz channel cabling system.


An enhanced version of the modular 5124-series panel has recently been launched as a separate product (6124-series). Together with the improved version of the 5618/19-x6x series of outlets and a tested cable the panel constitutes a "Cat. 6, Class E" Permanent Link with good margin.

The modular panels are available in shielded and unshielded versions in brushed aluminium material. Both versions are equipped with finger-screw strain relieves (a tool is available) to secure the cables, and to ensure proper connection between the shield of the cable and the panel when the shield is used.


See Product sheet on "Accessories" (PP9812UK) for detailed information on Telesafe's wide range of cable guides, mounting boards, patch cable organisers and cover plates.

All panels are manufactured out of 100% recyclable material.

15 year product guarantee.



5124-111 24-ports panel in brushed aluminium, 1U.



5104-120
4-ports module



4100-202
Cover plate, black



4905-00
Tool for fingerscrews

For ordering information and electrical parameters, see next page

Electrical parameters

Electrical Parameters	Measured Values 100MHz e-type	Measured Values 250 Mhz
Attenuation/Insertion Loss	0,2	0,2
NEXT pair-to-pair	58,0	49,0
FEXT pair-to-pair	47,0	38,0
Return Loss	25,0	13,0

Electrical parameters for a typical Permanent Link Class E in combination with the 5618 series of wall outlets.

Ordering information

Modular Patch Panels	Shielded	Unshielded
24-ports (6 x 4 modules), 1U	5124-111	5124-011
24-ports (6 x 4 modules), 1U, Class E, permanent link	6124-111	6124-011
16-ports (4 x 4 modules), 1U	5116-111	5116-011
Chassis, empty	4100-111	4100-011
4-port module	5104-120	5104-020
4-port module, Class E, permanent link	6104-120	6104-020
Other products		
Cover plate	4100-202	
Mounting Board	4710-501	
Tool for finger screws	4905-00	

Producer:



P.O. Box 234, N-1301 SANDVIKA, Norway
 Phone: +47 67807300 Fax: +47 67807301
 E-mail: sales@telesafe.no, Internet: www..telesafe.com

Distributor: