

Mini Patch Boxes

Telesafe has developed a series of aluminium-encased Mini Patch Boxes which can be used for small offices where a 19" cabinet or the 10" MiniRack from Telesafe is not needed. The Mini Patch Boxes may also be used as a distributor for clusters of users as an alternative to multiple outlets or as a consolidation point. The boxes have two holes for screw mounting on a wall or in a shelf.

The Mini Patch Boxes from Telesafe meet the electrical specifications of the latest ISO/IEC 11801 and Cenelec 50173 standards.

Telesafe's Mini Patch Boxes may also be delivered in an enhanced version. Together with the improved version of the 5618/19-x6x series of outlets and a tested cable, the enhanced Mini Patch Boxes constitute a "Cat. 6, Class E" Permanent Link with good margin.

The Mini Patch Boxes are available with 4, 8 and 12 ports, unshielded and shielded.

The Mini Patch Boxes are manufactured out of 100% recyclable material.

15 year product guarantee



4, 8 and 12 ports, unshielded



5304-111

4-port, shielded



5308-111

8-port, shielded



5312-111

12-port, shielded

For ordering information, see next page

Electrical parameters

Electrical Parameters	Measured Values 100MHz e-type	Measured Values 250 Mhz
Attenuation/Insertion Loss	0,2	0,2
NEXT pair-to-pair	58,0	49,0
FEXT pair-to-pair	47,0	38,0
Return Loss	25,0	13,0

Electrical parameters for a typical Permanent Link Class E in combination with the 5618 series of wall outlets.

Dimensions

	Width	Depth	Height
4-port	95 mm	89 mm	33 mm
8-port	165 mm	89 mm	33 mm
12-port	236 mm	89 mm	33 mm

Ordering information

MiniPatch Boxes	Unshielded	Shielded
Aluminium housing		
4xRJ45	5304-011	5304-111
4xRJ45, Class E, permanent link	6304-011	6304-111
8xRJ45	5308-011	5308-111
8xRJ45, Class E, permanent link	6308-011	6308-111
12xRJ45	5312-011	5312-111
12xRJ45, Class E, permanent link	6312-011	6312-111

Producer:



P.O. Box 234, N-1301 SANDVIKA, Norway
 Phone: +47 67807300 Fax: +47 67807301
 E-mail: sales@telesafe.no, Internet: www..telesafe.com

Distributor: