

## 5618 Wall Outlets

These top of the line outlets come with spring loaded shutters as standard on the angled version, and regular dust covers on the straight version. Easy installation is ensured as the entire outlet has only two screws, one for the strain relief and one for the centre plate. The easily readable labelling field and the snap-on shielding cover completes this slim, steel housed outlet.

The 5618 series of outlets meet the electrical specifications of the latest ISO/IEC 11801 and CENELEC 50173 standards. The angled outlet, with spring loaded shutters, has recently been enhanced and may together with the 6124-series of patch panels and a tested cable constitute a "Cat. 6, Class E" Permanent Link with good margin.

### Some features:

- Shielded and unshielded, single and double, angled and straight outlet
- Two colours are standard, Ivory (RAL 1030) and White (RAL 9010).
- Cable access from both sides.
- Spring loaded dust covers are standard for the angled version. Without is optional.
- Two screws, one for the strain relief and one for the centre plate. Snap-on shielding cover.
- Slim, only 24mm deep, in steel housing for maximum EMC performance (3 times better than moulding).

See Product sheet on "Accessories" (WO9807UK) for detailed information on Telesafes wide range of frames, adapters, wall boxes and installation brackets.

All outlets are manufactured out of non-toxic and 100% recyclable material.

### 15 year product guarantee



## Electrical parameters

Electrical Parameters	Measured Values 100MHz e-type	Measured Values 250 Mhz
Attenuation/Insertion Loss	0,2	0,2
NEXT pair to pair	53,0	43,0
FEXT pair to pair	40,0	35,0
Return Loss	22,0	16,0

Electrical parameters for a typical Permanent Link Class E in combination with the 6124-x11 series of patch panels

## Ordering information

Trunk Mounting Outlets	Shielded		Unshielded	
	Ivory (RAL 1013)	White (RAL 9010)	Ivory (RAL 1013)	White (RAL 9010)
<b>Straight</b>				
1 x RJ45, no frame	5618-1512	5618-1513	5618-0512	5618-0513
1 x RJ45, w/EURO frame	5618-151	5618-1511	5618-051	5618-0511
2 x RJ45, no frame	5618-1522	5618-1523	5618-0522	5618-0523
2 x RJ45, w/EURO frame	5618-152	5618-1521	5618-052	5618-0521
<b>Angled</b>				
1 x RJ45, no frame	5618-1612	5618-1613	5618-0612	5618-0613
1 x RJ45, w/EURO frame	5618-161	5618-1611	5618-061	5618-0611
2 x RJ45, no frame	5618-1622	5618-1623	5618-0622	5618-0623
2 x RJ45, w/EURO frame	5618-162	5618-1621	5618-062	5618-0621
<b>Wall Mounting Outlets</b>				
<b>Straight.</b>				
1 x RJ45, with 32 mm box, and TS-frame 80x80 mm	5618-1564	5618-1565	5618-0564	5618-0565
2 x RJ45, with 32 mm box, and TS-frame 80x80 mm	5618-1574	5618-1575	5618-0574	5618-0575
<b>Angled.</b>				
1 x RJ45, with 32 mm box, and TS-frame 80x80 mm	5618-1664	5618-1665	5618-0664	5618-0665
2 x RJ45, with 32 mm box, and TS-frame 80x80 mm	5618-1574	5618-1575	5618-0574	5618-0575
<b>Accessories</b>				
<b>Frames:</b>	<b>Ivory (RAL 1013)</b>	<b>White (RAL 9010)</b>		
EURO frame, 80x80mm	4718-50	4718-501		
Single TS-frame, 80x80mm	4718-300	4718-301		
Double TS-frame, 80x150mm	4718-400	4718-401		
Single TS-frame, 84x84mm	4718-200	4718-201		
<b>Wall boxes:</b>				
32 mm, 80x80mm, no frame	4718-1120	4718-1121		
40mm, 84x84 mm, no frame	4718-1110	4718-1111		
32mm, 80x80 mm, with frame	4718-1020	4718-1021		
40mm, 84x84mm, with frame	4718-1010	4718-1011		

**Producer:**



P.O. Box 234, N-1301 SANDVIKA, Norway  
 Phone: +47 67807300 Fax: +47 67807301  
 E-mail: sales@telesafe.no, Internet: www..telesafe.com

**Distributor:**