

## 55xx Wall Outlets

These outlets are designed with a 45x45mm sized centre plate and mechanics that fits directly into small cable trunks and floor tanks.

The outlet, which is casted in a zinc alloy, is easy to install. There is only one screw which is on the strain relief. The cable can be accessed from both sides. The shielding cover with the strain relief may be turned 180 degrees around.

The 55xx series of outlets meet the electrical specifications of the latest ISO/IEC 11801 and CENELEC 50173 standards. The outlets may be installed in a "mix and match" Class D (100 MHz, Cat 5e) cabling solutions, or as one component in a Class E 250 MHz channel cabling system.

### Some features:

- Shielded and unshielded, double, straight outlet
- Two colours are standard, Ivory and White.
- Cable access from either side. Snap-on shielding cover.
- Snaps directly into different 45mm trunk and frame systems.
- Moulded, zinc alloy.

All outlets are produced of non-toxic and 100% recyclable materials.

**15 year product guarantee.**



## Ordering information

<b>55xx Wall Outlets</b> Straight	<b>Shielded</b>		<b>Unshielded</b>	
	<b>Ivory (RAL1013)</b>	<b>White (RAL9010)</b>	<b>Ivory (RAL1013)</b>	<b>White (RAL9010)</b>
<b>For trunk mounting</b> 2 x RJ45, 45x45mm	5551-121	5551-122	5551-021	5551-022
<b>For frame mounting</b> 2 x RJ45, 45x45mm	5571-121	5571-122	5571-021	5551-071

**Producer:**

P.O. Box 234, N-1301 SANDVIKA, Norway  
Phone: +47 67807300 Fax: +47 67807301  
E-mail: [sales@telesafe.no](mailto:sales@telesafe.no), Internet: [www.telesafe.com](http://www.telesafe.com)

**Distributor:**